

Designation by IEC	Designation by GB	Rated Voltage	Rated Temperature	Nominal crossection(mm')	Description	Application
60227 IEC 01	BV	450V/750V	0°C~70°C	1.5 to 35mm <sup>2</sup>	Copper Conductor PVC Insulated Rigid Cable	Fixed laid indoors instrument etc.
60227 IEC 05	BVR	450V/750V	0°C~70°C	2.5 to 35mm <sup>2</sup>	copper conductor PVC Insulated Semi-Flexible	For laying permanent place where flexible required
60227 IEC 02	RV	450V/750V	0°C~70°C	1.5 to 35mm <sup>2</sup>	Copper conductor PVC Insulated	Mainly used at middle and light style moving electronics, home appliances, power and lighting and the places v/here flexible required
60227 IEC 06	RV	300V/500V	0°C~70°C	0.5 to 1mm <sup>2</sup>		
60227 IEC 52	RVV	300V/300V	0°C~70°C	0.5 to 0.75mm <sup>2</sup> (2 to 3 cores)	Copper conductor PVC Insulated and PVC Sheathed Round Flexible Connector Cable	
60227 IEC 53	RVV	300V/500V	0°C~70°C	0.75 to 2.5mm <sup>2</sup> (2 to 5 cores)		
				4mm <sup>2</sup> (3 to 5 cores)		
				0.75 to 2.5mm <sup>2</sup> (6 cores)		
				0.75 to 1.5mm <sup>2</sup> (7 to 8 cores)		
				0.75 to 1mm <sup>2</sup> (10 to 24 cores)		
60227 IEC 42	RVB	300V/300V	0°C~70°C	0.5 to 4mm <sup>2</sup> (2 cores)	Copper conductor PVC Insulated Flat Flexible Connector Cable	
N/A	RVVP	300/300V	0°C~70°C	0.08 to 1.5mm <sup>2</sup> (2 cores)	PVC Insulated Wire and Shielded Wire for Installation	For Installation
				0.12 to 1.5mm <sup>2</sup> (3 cores)		
				0.12 to 0.4mm <sup>2</sup> (4 to 24 cores)		
	AVVR	300/300V	0°C~70°C	0.08 to 0.4mm <sup>2</sup> (2 cores)		
				0.12 to 0.4mm <sup>2</sup> (4 to 24 cores)		