

Number of Elements	Cross section core mm ²	Electrical Cross section braid mm ²	Conductor Diameter mm	Insulation Thickness mm	Thickness Inner Covering mm	Diameter Inner Covering mm	Diameter Braid Wire mm	Mechanical cross-section of the braid mm ²	Thickness Outer Sheath mm	Diameter Outer Sheath mm	Weight of Cable Approx. (kg/km)
1	25	20	6.5	4.5	1.0	22.0±1.0	0.4	35	1.8	28.0±1.5	1370
1	35	20	7.4	4.5	1.0	23.0±1.5	0.4	27.1	1.8	29.0±1.5	1500
1	50	20	8.8	4.5	1.0	24.0±1.5	0.4	27.1	1.9	30.5±.5	1700
1	70	20	10.3	4.5	1.0	26.0±1.5	0.4	27.1	1.9	32.0±1.5	2000
1	95	20	12.1	4.5	1.2	28.0±1.5	0.4	31.7	2.0	34.5±2.0	2450
1	120	20	13.6	4.5	1.2	29.5±1.5	0.4	31.7	2.0	36.0±2.0	2700
1	150	20	15.1	4.5	1.2	31.0±1.5	0.4	31.7	2.1	38.0±2.0	3000
1	185	20	16.8	4.5	1.2	33.0±1.5	0.4	31.7	2.2	39.5±2.5	3500
1	240	25	19.1	4.5	1.2	35.0±1.5	0.4	36.2	2.3	42.0±2.5	4300
1	300	29	21.5	4.5	1.2	37.5±1.5	0.4	40.7	2.4	44.5±2.5	5000
1	400	30	25.6	4.5	1.5	42.0±2.0	0.4	49.8	2.6	49.5±2.5	6250