

SIZE CHART

Nominal Cross Section	Diameter of Conductor (Approx.)	Nominal Insulation Thickness	Nominal Sheath Thickness	Overall Diameter (Approx.)
mm ²	mm	mm	mm	mm
1x4	2.3	1	1.4	7.1
1x6	2.8	1	1.4	7.6
1x10	3.6	1	1.4	8.4
1x16	4.5	1	1.4	9.3
1x25	5.6	1.2	1.4	10.8
1x35	6.7	1.2	1.4	11.9
1x50	8	1.4	1.4	13.6
1x70	9.4	1.4	1.4	15.1
1x95	11	1.6	1.5	17.2
1x120	12.4	1.6	1.5	18.7
1x150	13.8	1.8	1.6	20.6
1x185	15.3	2	1.7	22.7
1x240	17.5	2.2	1.8	25.4
1x300	19.5	2.4	1.9	28
1x400	22.6	2.6	2	31.7
1x500	25.2	2.8	2.1	35
1x630	28.3	2.8	2.2	38.3
3x1.5	1.4	0.8	1.8	10.1
3x2.5	1.8	0.8	1.8	10.9
3x4	2.3	1	1.8	12.9
3x6	2.8	1	1.8	13.9
3x10	3.6	1	1.8	15.7
3x16	4.5	1	1.8	17.6
3x25	5.6	1.2	1.8	20.8
3x35	6.7	1.2	1.8	23.2
3x50	8	1.4	1.8	26.9
3x70	9.4	1.4	1.9	30.1
3x95	11	1.6	2.1	34.7
3x120	12.4	1.6	2.2	38
3x150	13.8	1.8	2.3	42.1
3x185	15.3	2	2.5	46.5
3x240	17.5	2.2	2.7	52.5
3x300	19.5	2.4	2.8	58
3x400	22.6	2.6	3.1	66.1
4x1.5	1.4	0.8	1.8	10.8
4x2.5	1.8	0.8	1.8	11.8
4x4	2.3	1	1.8	14
4x6	2.8	1	1.8	15.2
4x10	3.6	1	1.8	17.1
4x16	4.5	1	1.8	19.3
4x25	5.6	1.2	1.8	22.9
4x35	6.7	1.2	1.8	25.6
4x50	8	1.4	1.9	29.9
4x70	9.4	1.4	2	33.5
4x95	11	1.6	2.2	38.7
4x120	12.4	1.6	2.3	42.3
4x150	13.8	1.8	2.5	46.9
4x185	15.3	2	2.6	51.9
4x240	17.5	2.2	2.9	58.6
4x300	19.5	2.4	3.1	64.8
4x400	22.6	2.6	3.3	73.8